

1

2

3

4

5

6

7

8

The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements

RoHS

A±0.20

4.20±0.20

5.40

10.10±0.50

Circuit 1

C±0.30

19.70

10.8

B±0.40

2PIN

3PIN

4PIN

5PIN

6PIN

VERTICAL VIEW 0.8:1

3.40

15.0

7.40

3D view 0.5:1

NOTE:

1.MATERIAL SPECIFICATION:
1-1.HOUSING: PA66

2.MECHANICAL PERFORMANCE:
2-1.RETENTIVITY FORCE: 2.5KGF/pin min
2-2.DURABILITY: 30 CYCLES.

3.ELECTRICAL PERFORMANCE:
3-1.CURRENT RATING: 9A
RATED VOLTAGE : 600V AC/DC
3-2.CONTACT RESISTANCE: 30 mΩ MAX
3-3.INSULATION RESISTANCE: 1000MΩ Min
3-4.DIELECTRIC WITHSTANDING : 1500V

4.ENVIRONMENTAL PERFORMANCE:
4-1.OPERATING TEMPERATURE: -25°C~+85°C.

5.PACKAGE SPEC: PE BAG

6.P/N:

SERIES NO:

CONNECTOR:

MALE FEMALE:

ROW NO:

C4201

H

M-1

XX

X

X

WATER CODE

0-UL94V-0

2-UL94V-2

3-UL94V-0+HF

COLOR:

A-BLACK

K-WHITE

S-NATURE

PIN Q'PY:

02~06

Ordering Information& Dimensions

Poles	Dimensions (mm)		
	A	B	C
02P	4.20	9.60	7.50
03P	8.40	13.80	11.60
04P	12.60	18.00	15.80
05P	16.80	22.20	20.20
06P	21.00	26.60	24.10

REV.	REVISION RECORD	DATE	UNIT:mm SIZE: A4	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:	万连科技 WanLian Teconology Co., Ltd
A0	NEW RELEASE	21.11.17		LINEAR	ANGLES	APPROVED	Wang_jr	21.11.17	C4201HM-1XXXX	ENDE05	
				0.0±0.35	X°REF±6°	DESIGNER	Han_Gao	21.11.17	TITLE:		
				0.00±0.25	X°±3°	DRAWN	Zijun_Huang	21.11.17	Pitch 4.2mm Male 单排 Housing		
			0.000±0.10	X°X'±2°						REV: A0	SHEET: 1/1