

1	2	3	4	5	6	7	8																																																																								
The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements																																																																															
A	RoHS							A																																																																							
B								B																																																																							
C								C																																																																							
D								D																																																																							
E								E																																																																							
F	NOTE: 1.MATERIAL SPECIFICATION: 1-1.CONTACTS: PHOSPHOR BRONZE 2.PLATING SPECIFICATION: 2-1.CONTACTS: TIN/GOLD FLASH PLATED OVER ALL. 3.ELECTRICAL PERFORMANCE: 3-1.CURRENT RATING: 1A RATED VOLTAGE : 125V AC/DC 3-2.CONTACT RESISTANCE: 30 mΩ MAX 3-3.INSULATION RESISTANCE: 100MΩ Min 3-4.DIELECTRIC WITHSTANDING : 500V 4.ENVIRONMENTAL PERFORMANCE: 5-1.OPERATING TEMPERATURE: -25°C~+85°C. 5.PACKAGE SPEC:PAPER PLATE 6.P/N: SERIES NO: A1251 T 1 F X-X CONNECTOR: T-TERMINAL TYPE CODE MALE FEMALE: F-FEMALE M-MALE PLATING: 1-G/F A-ALL AU G/F C-BRIGHT TIN D-MATTE TIN METAL: P-PHOSPHOR BRONZE B-BRASS							F																																																																							
G								G																																																																							
H	<table><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td rowspan="4"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td>PART.NO:</td><td>DWG.NO:</td><td rowspan="4"></td></tr><tr><td>A0</td><td>NEW RELEASE</td><td>21.10.12</td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td>Wang_jr</td><td>21.10.12</td><td colspan="2">A1251T1FX-X</td><td>ENDE05</td></tr><tr><td></td><td></td><td></td><td>0.0±0.35</td><td>X'REF±6°</td><td>DESIGNER</td><td>Han_Gao</td><td>21.10.12</td><td colspan="2">TITLE:</td><td></td></tr><tr><td></td><td></td><td></td><td>0.00±0.25</td><td>X'±3°</td><td>DRAWN</td><td>Zijun_Huang</td><td>21.10.12</td><td colspan="2">Pitch1.25mm 母端子 AWG # 26~# 32</td><td></td></tr><tr><td></td><td></td><td></td><td>UNIT:mm</td><td>0.00±0.25</td><td>X'±3°</td><td></td><td></td><td></td><td colspan="2"></td><td>REV: A0</td><td>SHEET: 1/1</td></tr><tr><td></td><td></td><td></td><td>SIZE: A4</td><td>0.000±0.10</td><td>X'X' ±2°</td><td></td><td></td><td></td><td colspan="2"></td><td></td><td></td></tr></table>							REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:		A0	NEW RELEASE	21.10.12	LINEAR	ANGLES	APPROVED	Wang_jr	21.10.12	A1251T1FX-X		ENDE05				0.0±0.35	X'REF±6°	DESIGNER	Han_Gao	21.10.12	TITLE:						0.00±0.25	X'±3°	DRAWN	Zijun_Huang	21.10.12	Pitch1.25mm 母端子 AWG # 26~# 32						UNIT:mm	0.00±0.25	X'±3°						REV: A0	SHEET: 1/1				SIZE: A4	0.000±0.10	X'X' ±2°								H
REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:																																																																					
A0	NEW RELEASE	21.10.12		LINEAR	ANGLES	APPROVED	Wang_jr	21.10.12	A1251T1FX-X				ENDE05																																																																		
				0.0±0.35	X'REF±6°	DESIGNER	Han_Gao	21.10.12	TITLE:																																																																						
				0.00±0.25	X'±3°	DRAWN	Zijun_Huang	21.10.12	Pitch1.25mm 母端子 AWG # 26~# 32																																																																						
			UNIT:mm	0.00±0.25	X'±3°						REV: A0	SHEET: 1/1																																																																			
			SIZE: A4	0.000±0.10	X'X' ±2°																																																																										
1	2	3	4	5	6	7	8																																																																								