



Note: 11007TOP-XX-NK
Finish _____ No Mark
0A--Gold-flash 0B--2u" 0C--3u"
0D--4u" 0E--5u" 0F--10u"
0G--15u" 0H--30u" 0I--50u"

The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reef
11007TOP-2E-NK	AWG #28~#32	0.80mm(max)	Phosphor Bronze	Tin-Plated	20,000 pcs
11007TOP-0A-NK	AWG #28~#32	0.80mm(max)	Phosphor Bronze	Gold-plated 0.8u" on contact area	20,000 pcs
11007TOP-0C-NK	AWG #28~#32	0.80mm(max)	Phosphor Bronze	Gold-plated 3u" on contact area	20,000 pcs
11007TOP-3E-NK	AWG #28~#32	0.80mm(max)	Phosphor Bronze	Matte Tin plated	20,000 pcs

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO:	
C2	新增电镀规格	15.07.09	LINEAR	1:1					11007TOP-XX-NK
C3	变更公司名称	17.03.27	0.0±0.25	APPROVED					DWG. NO:
C4	依TN1709280140没变	17.03.27	X° RHF±6°	DESIGNER					ENDE05
C5	依TN1809140180新增规格	18.09.14	0.00±0.15	DRAWN	黄小锋	18.09.14			REV: C5 SHEET: 1/1

