



11256H00-NPX-HF-NK
① ② ③④⑤ ⑥

- ① Series No.
- ② H90 : Side Contact
H00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color (A--Y)
Blank : Natural type
- ⑤ HF : Halogen Free
- ⑥ NK : No Mark
Blank : Mark

Specifications:
 Rated Voltage : 100V AC/DC
 Rated Current : 1A AC,DC
 Withstand Voltage : 500V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 500MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the *WI-PZ-142* HSF technical standard control requirements



Circuits Part No	Dimensions			
	A	B	C	D
2P	1.25	6.00	3.80	
3P	2.50	7.25	5.05	
4P	3.75	8.50	6.30	
5P	5.00	9.75	7.55	
6P	6.25	11.00	8.80	
7P	7.50	12.25	10.05	6.25
8P	8.75	13.50	11.30	7.50
9P	10.00	14.75	12.55	8.75
10P	11.25	16.00	13.80	10.00
11P	12.50	17.25	15.05	11.25
12P	13.75	18.50	16.30	12.50
13P	15.00	19.75	17.55	13.75
14P	16.25	21.00	18.80	15.00
15P	17.50	22.25	20.05	16.25
20P	23.75	28.50	26.30	22.50
24P	28.75	33.50	31.30	27.50
25P	30.00	34.75	32.55	28.75
30P	36.25	41.00	38.80	35.00

Suitable for JCTC 11256 series terminal

Part No.	Material	Color
11256H00-NP	Nylon 66,UL 94V-0	本色
11256H00-NP-NK	Nylon 66,UL 94V-0	本色
11256H00-NPA	Nylon 66,UL 94V-0	黑色
11256H00-NPA-NK	Nylon 66,UL 94V-0	黑色
11256H00-NP-HF	Nylon 66,UL 94V-0	本色无齿
11256H00-NPA-HF	Nylon 66,UL 94V-0	黑色无齿
11256H00-NP-HF-NK	Nylon 66,UL 94V-0	本色无齿
11256H00-NPA-HF-NK	Nylon 66,UL 94V-0	黑色无齿

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO.:
C4	依实物增加三角符号	13. 08. 13	LINEAR	1:1				11256H00-NPX-XX-XX
C5	HN1511030171	15. 11. 27	0.0±0.25	APPROVED				DWG. NO.:
C6	更换公司名称	17. 03. 24	0.00±0.15	DESIGNER				ENDE05
D0	HN1811230212	18. 11. 23	0.000±0.08	DRAWN	Jerry	18. 11. 23	REV: D0 SHEET: 1/1	