



Circuits No.	Dimensions		
	A	B	C
2P	2.00	5.80	4.60
3P	4.00	7.80	6.60
4P	6.00	9.80	8.60
5P	8.00	11.80	10.60
6P	10.00	13.80	12.60
7P	12.00	15.80	14.60
8P	14.00	17.80	16.60
9P	16.00	19.80	18.60
10P	18.00	21.80	20.60
11P	20.00	23.80	22.60
12P	22.00	25.80	24.60
13P	24.00	27.80	26.60
14P	26.00	29.80	28.60
15P	28.00	31.80	30.60
16P	30.00	33.80	32.60

Suitable for JCTC 12001 series terminal

Part No.	Material	Notes
12001H00-NP	Nylon 66,UL94V-0	本色
12001H00-NP-NK	Nylon 66,UL94V-0	本色
12001H00-NPA	Nylon 66,UL94V-0	黑色
12001H00-NPA-NK	Nylon 66,UL94V-0	黑色
12001H00-NPE	Nylon 66,UL94V-0	黄色
12001H00-NP-HF	Nylon 66,UL94V-0	本色无卤
12001H00-NP-HF-NK	Nylon 66,UL94V-0	本色无卤
12001H00-NPA-HF	Nylon 66,UL94V-0	黑色无卤
12001H00-NPC-HF	Nylon 66,UL94V-0	红色无卤
12001H00-NPE-HF	Nylon 66,UL94V-0	黄色无卤
12001H00-NPF-HF	Nylon 66,UL94V-0	绿色无卤
12001H00-NPG-HF	Nylon 66,UL94V-0	蓝色无卤
12001H00-NPK-HF	Nylon 66,UL94V-0	白色无卤
12001H00-NPP-HF	Nylon 66,UL94V-0	蓝色无卤
12001H00-NPR-HF	Nylon 66,UL94V-0	红色无卤
12001H00-NP-HF-01	Nylon 66,UL94V-0	本色无卤 料号2306

- 12001H00-NPX-HF-NK
① ② ③④ ⑤ ⑥
- ① Series No.
 - ② H90 : Side Contact
H00 : Up Contact
 - ③ No. of Circuits
 - ④ X : Product color(A--Y)
Blank : Natural type
 - ⑤ HF : Halogen Free
 - ⑥ NK : No Mark
Blank : Mark

Specifications:
 Rated Voltage : 100V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WL-PZ-142"HSF technical standard control requirements

REV.	REVISION RECORD	DATE
D1	新增绿色规格	15.09.01
D2	更新公司名称	17.03.09
D3	依HN1808170152设变	18.08.17
D4	HN1907290162	19.07.29

SCALE:	NAME	DATE	GENERAL TOLERANCES	
			LINEAR	ANGLES
1:1			0.0±0.25	X° REF±6°
APPROVED			0.00±0.15	X° ±3°
DESIGNER			0.000±0.08	X° X'±2°
DRAWN	伍文聪	19.07.29		

2019.07.30
JCTC 胜蓝科技股份有限公司
 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司
 技术文件 发行章
 TITLE: PH 2.0mm PITCH HOUSING

PART. NO:	
12001H00-NPX-XX-XX	
DWG. NO:	
ENDE05	
REV:	SHEET:
D4	1/1