



12001TOP-XX-1X
 Die No.
 1A:A号模
 1B:B号模
 Finish

The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
12001TOP-2-1X	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Tin-plated On Ni	10,000 PCS
12001TOP-2E-1C	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Tin-plated On Ni	10,000 PCS
12001TOP-2E	AWG #24~#28	0.9-1.5mm	Phosphor Bronze	Tin-plated 60u"Min.	10,000 PCS
12001TOP-0A	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Gold Flash On Contact Area	10,000 PCS
12001TOP-5A	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Au 1u"Min On All	10,000 PCS
12001TOP-5C	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Au On All,Au 3u"Min On Contact Area	10,000 PCS

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	PART. NO:
C4	增加 "5A" 规格	16.04.11	LINEAR	1:1			12001TOX-XX-1X
C5	更新公司名称	17.03.09	0.0±0.25	APPROVED			DWG. NO:
C6	依TN1808170151设变	18.08.20	X° REF±6°	DESIGNER			ENDE05
D1	依TN1901070005设变	19.01.07	X° ±3°	DRAWN			REV: D1 SHEET: 1/1
			0.00±0.15				
			X° X'±2°				

JCTC 胜蓝科技股份有限公司
 TERMINAL&CONNECTORS 东莞市嘉智达电子科技有限公司
 TITLE: PH2.0端子