



F Specification & Ordering Information:

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel	Note
12002TOP-2E	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Tin-plated 60μ"Min	1,0000 PCS	plating after Stamping
12002TOP-0A	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Gold-flash	1,0000 PCS	plating after Stamping
12002TOP-0C	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Gold-plated 3u"	1,0000 PCS	plating after Stamping
12002TOP-0G	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Gold-plated 15u"	1,0000 PCS	plating after Stamping
12002TOP-0H	AWG #24~#28	1.50mm(max)	Phosphor Bronze	Gold-plated 30u"	1,0000 PCS	plating after Stamping

The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE:	NAME	DATE	<b>JCTC</b> ® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司  PART. NO: 12002TOP-XX-XX  DWG. NO: ENDE05  REV: D0 SHEET: 1/1	
C4	TN1404170045	14. 04. 17	LINEAR 0.00±0.25	ANGLES X° REF±6°	1:1	APPROVED	王志刚		14. 09. 19
C5	新增“OH”规格	14. 06. 26			0.00±0.15	X° ±3°	DESIGNER		肖坤权
C6	依JST修正Insulation O.D.	14. 09. 19	0.000±0.08	X° X'±2°	DRAWN	伍文聪	17. 07. 25		
D0	更新公司名称	17. 07. 25			TITLE: PHD2.0端子				