



12002W00-NP-L-F-HF
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② W90 : Side Contact
W00 : Up Contact
- ③ No. of Circuits
- ④ L : With Lock
- ⑤ F : With Boss
- ⑥ HF : Halogen Free

Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

PART NO.	Dimensions	
	A	B
2P	--	6.00
3P	4.00	8.00
4P	6.00	10.00
5P	8.00	12.00
6P	10.00	14.00
7P	12.00	16.00
8P	14.00	18.00
9P	16.00	20.00
10P	18.00	22.00
11P	20.00	24.00
12P	22.00	26.00
13P	24.00	28.00
14P	26.00	30.00
15P	28.00	32.00
16P	30.00	34.00



Part No.	Insulator	Color	Contact
12002W00-NP-L-F-HF	Nylon 66+15%GF,UL94V-0	Natural(White)	Brass/Tin-plated

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC ® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司 TITLE: PA 2.00mm PITCH DIP TYPE WAFER	PART. NO:
C0	新图面发行	14. 10. 28	LINEAR	1:1				12002W00-NP-L-F-HF
C1	更新公司名称	17. 05. 27	ANGLES	APPROVED				DWG. NO:
			0.0±0.25	DESIGNER				ENDE05
			0.00±0.15	DRAWN	伍文聪	17. 05. 27		REV: C1 SHEET: 1/1