



Specifications:  
 Rated Voltage : 250V AC/DC  
 Rated Current : 3A AC,DC  
 Withstand Voltage : 800V AC/minute  
 Contact Resistance : 10mΩ(MAX.)  
 Insulation Resistance : 1000MΩ(MIN.)  
 Temperature Range : -25°C~+85°C  
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

12002W00-NP-SF-XX-01-HF-XX-R  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

- ① Series No.
- ② W90 : Side Contact
- ③ No. of Circuits
- ④ S : SMT TYPE
- ⑤ F : A TYPE
- ⑥ Blank : Bright-Tin
- 3E : Matte-Tin
- ⑦ 01 : Without 2,3 PIN
- ⑧ HF : Halogen Free
- ⑨ NK : No Mark
- ⑩ R : Tape & Reel(With Cap)

Part No.	Insulator	Cap	PIN/Solder Tabs
12002W00-NP-SF-01-HF-R	High temperature plastic, UL94V-0/Natural(Beige)	High temperature plastic, UL94V-0	Brass/Bright Tin-plated
12002W00-NP-SF-01-HF-NK-R			Brass/Bright Tin-plated
12002W00-NP-SF-3E-01-HF-NK-R			Brass/Matte Tin-plated

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 <b>JCTC</b> <sup>®</sup> <b>TERMINAL&amp;CONNECTORS</b>			
AO	新图面发行	21.10.29	LINEAR	ANGLES	1:1			12002W00-NP-SA-XX-01-HF-XX-R	ENDE05				
			0.0±0.25	X° REF±6°	APPROVED			TITLE PA 2.00mm PITCH 180° SMT WAFER					
			0.00±0.15	X° ±3°	DESIGNER								
			UNIT: MM	0.00±0.08	X° X' ±2°	DRAWN	HZJ		21.10.29				
			SIZE: A4							REV	AO	SHEET	1/2