



Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 1000V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

12003H00-2x5PA-K1-I-HF

- ① Series No.
- ② H90 : Side Contact
H00 : Up Contact
- ③ No. of Circuits
- ④ A : Product color(A--Y)
Blank: Natural type
- ⑤ K1 : #1 KEYED
- ⑥ T : Mount type
- ⑦ HF: Halogen Free

Suitable for JCTC 12003 series terminal

Part No.	Material	Color
12003H00-2x5PA-K1-T-HF	Nylon66,UL 94V-0	Black

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	PART NO:
A0	新图面发行	16.11.28	LINEAR 0.0±0.25	1:1	APPROVED		12003H00-2x5PA-K1-T-HF
			ANGLES X° REF±6°		DESIGNER		DWG. NO:
			0.00±0.15		DRAWN		ENDE05
			X° ±3°				REV: A0
			0.000±0.08				SHEET: 1/1
			X° X'±2°				

JCTC 胜蓝科技股份有限公司
 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司

TITLE:
DB双排 2.0mm PITCH HOUSING