



PART NO:  
12003TOP-XX-J-NK

Finish: 0A--Gold-flash, 0B--2u", 0C--3u", 0D--4u", 0E--5u", 0F--10u", 0G--15u", 0H--30u", 0I--50u"

NK: No Mark  
Blank: Mark

紧端: 适用16PIN位以下规格

Specification & Ordering Information:

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
12003TOP-0A-J-NK-01	AWG #26~#30	1.35mm(max)	Phosphor Bronze	1u" Au on Contact Area.	15,000 PCS
12003TOP-0X-J-NK	AWG #26~#30	1.35mm(max)	Phosphor Bronze	Gold Plated on Contact Area.	15,000 PCS

The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements

REV.	REVISION RECORD	DATE	UNIT: MM	SIZE: A4	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
					LINEAR	ANGLES			
C0	新图面发行	10.01.19			0.00±0.15	X° REF±6°			
C1	TR1105310082	11.05.31			0.00±0.15	X° ±3°			
C2	变更公司名称	17.07.20			0.00±0.15	X° ±3°			
C3	TR2002180016	20.02.18			0.000±0.08	X° X'±2°		伍文聪	20.02.18

**JGTC** 胜蓝科技股份有限公司  
TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司

PART NO: 12003TOP-XX-J-NK

DWG. NO: ENDE05

TITLE: p3

DB2.0端子

REV: C3 SHEET: 1/1