



PART NO:  
12003TOP-XX-J-NK

Finish: NK: No Mark  
Blank: Mark

紧端: 适用16PIN位以下规格

0A--Gold-flash	0B--2u"	0C--3u"
0D--4u"	0E--5u"	0F--10u"
0G--15u"	0H--30u"	0I--50u"

Specification & Ordering Information:

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
12003TOP-0A-J-NK-01	AWG #26~#30	1.35mm(max)	Phosphor Bronze	1u" Au on Contact Area.	15,000 PCS
12003TOP-0X-J-NK	AWG #26~#30	1.35mm(max)	Phosphor Bronze	Gold Plated on Contact Area.	15,000 PCS

The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
C0	新图面发行	10.01.19		0.00±0.15	X° REF±6°	APPROVED		
C1	TR1105310082	11.05.31		0.00±0.15	X° ±3°	DESIGNER		
C2	变更公司名称	17.07.20	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	伍文聪	20.02.18
C3	TR2002180016	20.02.18						

**JGTC** 胜蓝科技股份有限公司  
TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司

PART NO: 12003TOP-XX-J-NK

DWG. NO: ENDE05

TITLE: p3

DB2.0端子

REV: C3 SHEET: 1/1