



PART NO:
12003TOP-XX-S-NK

Finish: NK: No Mark
Blank: Mark
松端: 适用17PIN位以上规格

0A--Gold-flash 0B--2u" 0C--3u"
0D--4u" 0E--5u" 0F--10u"
0G--15u" 0H--30u" 0I--50u"

Specification & Ordering Information:

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
12003TOP-0A-S-NK-01	AWG #26~#30	1.35mm(max)	Phosphor Bronze	1u" Au on Contact Area.	15,000 PCS
12003TOP-0X-S-NK	AWG #26~#30	1.35mm(max)	Phosphor Bronze	Gold Plated on Contact Area.	15,000 PCS
12003TOP-0X-S	AWG #26~#30	1.35mm(max)	Phosphor Bronze	Gold Plated on Contact Area.	15,000 PCS

The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements

REV.	REVISION RECORD		DATE	UNIT: MM	SIZE: A4	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	JGTC® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART NO: 12003TOP-XX-S-XX	
	DESCRIPTION	DATE				LINEAR	ANGLES					TITLE:p3	DWG. NO: ENDE05
C1	新增带字规格	10.12.14				0.00±0.15	X° REF±6°	APPROVED			DB2.0端子	REV: C4	SHEET: 1/1
C2	TR1105310082	11.05.31			0.00±0.08	X° X'±2°	DESIGNER						
C3	变更公司名称	17.07.20					DRAWN	伍文聪	20.02.18				
C4	TR2002180016	20.02.18											