



12005H00-NPX-L-HF

- ① Series No.
- ② H90 : Side Contact  
H00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)
- ⑤ L : Mount type
- ⑥ HF : Halogen Free

Specifications:  
 Rated Voltage : 250V AC/DC  
 Rated Current : 2A AC,DC  
 Withstand Voltage : 800V AC/minute  
 Contact Resistance : 20mΩ(MAX.)  
 Insulation Resistance : 1000MΩ(MIN.)  
 Temperature Range : -25°C~+85°C  
 The product using material and processing must conform to the "WI-PZ-142" HSF technical standard requirements

Circuits Part No	Dimensions			
	A	B	C	D
2P	5.60	4.60	2.00	2.30
3P	7.60	6.60	4.00	2.30
4P	9.60	8.60	6.00	4.30
5P	11.60	10.60	8.00	6.50
6P	13.60	12.60	10.00	6.50
7P	15.60	14.60	12.00	6.50
8P	17.60	16.60	14.00	12.20
9P	19.60	18.60	16.00	12.20
10P	21.60	20.60	18.00	14.50
11P	23.60	22.60	20.00	14.50
12P	25.60	24.60	22.00	14.50
13P	27.60	26.60	24.00	14.50
14P	29.60	28.60	26.00	14.50
15P	31.60	30.60	28.00	14.50
16P	33.60	32.60	30.00	14.50

Part No.	Material	Color
12005H00-NP-L	Nylon66,UL 94V-0	本色
12005H00-NPA-L	Nylon66,UL 94V-0	黑色
12005H00-NP-L-HF	Nylon66,UL 94V-0	本色无卤
12005H00-NPA-L-HF	Nylon66,UL 94V-0	黑色无卤
12005H00-NPC-L-HF	Nylon66,UL 94V-0	红色无卤
12005H00-NPM-L-HF	Nylon66,UL 94V-0	米黄色无卤
12005H00-NP-L-HF-NK	Nylon66,UL 94V-0	本色无卤

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO: 12005H00-NP-L-XX
C4	HR1105280083	14.02.21	LINER	1:1				
C5	增加黑色无卤规格	15.09.29	ANGLES	APPROVED				
C6	增加红色无卤规格	16.04.19	0.0±0.25 X° REF±6°	DESIGNER				
D0	变更公司名称	17.03.10	0.00±0.15 X° ±3°	DRAWN	伍文聪	17.03.10	REV: DO SHEET: 1/1	