



Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 1000V AC/minute
 Contact Resistance : 30mΩ(Max.)
 Insulation Resistance : 1000MΩ(Min.)
 Temperature Range : -25°C~+85°C
 Contact: Brass/Matte Tin-plated
 Material: Thermal Plasticity Resin, UL94V-0
 Halogen Free
 Color: Natural(Beige)
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Circuits	Dimensions		
	A	B	C
2P	--	6.00	1.50
3P	4.00	8.00	
4P	6.00	10.00	3.50
5P	8.00	12.00	5.50
6P	10.00	14.00	7.50
7P	12.00	16.00	9.50
8P	14.00	18.00	11.50
9P	16.00	20.00	13.50
10P	18.00	22.00	15.50
11P	20.00	24.00	
12P	22.00	26.00	
13P	24.00	28.00	
14P	26.00	30.00	
15P	28.00	32.00	
16P	30.00	34.00	

12005W00-NP-S1-3E-HF
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② W90 : Side Contact
W00 : Up Contact
- ③ No. of Circuits
- ④ S1: S1 TYPE
- ⑤ 3E: Matte Tin-plated
- ⑥ HF: Halogen Free

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	JCTC ® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO: 12005W00-NP-S1-3E-HF
C0	新图面发行	13.08.13		LINEAR	ANGLES	APPROVED: <i>[Signature]</i>				DWG. NO:
C1	更新公司名称	17.03.10		0.0±0.25	X° REF±6°	DESIGNER: <i>[Signature]</i>				ENDE05
			UNIT: MM	0.00±0.15	X° ±3°	DRAWN: 伍文聪			TITLE: 2.00mm PITCH DIP TYPE 180° WAFER	REV: C1 SHEET: 1/1
			SIZE: A4	0.000±0.08	X° X'±2°					