



Specifications:  
 Rated Voltage : 250V AC/DC  
 Rated Current : 3A AC,DC  
 Withstand Voltage : 1000V AC/minute  
 Contact Resistance : 30mΩ(Max.)  
 Insulation Resistance : 1000MΩ(Min.)  
 Temperature Range : -25°C~+85°C  
 Contact: Brass/Matte Tin-plated  
 Material: Thermal Plasticity Resin, UL94V-0  
 Halogen Free  
 Color: Natural(Beige)  
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

12005W90-NP-A-S1-3E-HF  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② W90 : Side Contact  
W00 : Up Contact
- ③ No. of Circuits
- ④ A: A TYPE
- ⑤ S1: S1 TYPE
- ⑥ 3E: Matte Tin-plated
- ⑦ HF: Halogen Free

Circuits	Dimensions		
	A	B	C
2P	--	8.00	1.50
3P	4.00	10.00	
4P	6.00	12.00	3.50
5P	8.00	14.00	5.50
6P	10.00	16.00	7.50
7P	12.00	18.00	9.50
8P	14.00	20.00	11.50
9P	16.00	22.00	13.50
10P	18.00	24.00	15.50
11P	20.00	26.00	
12P	22.00	28.00	
13P	24.00	30.00	
14P	26.00	32.00	
15P	28.00	34.00	
16P	30.00	36.00	

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	JCTC® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO:
C0	新图面发行	13.06.13	MM	LINEAR: 0.0±0.25	1:1	伍文聪	17.07.10		12005W90-NP-A-S1-3E-HF
C1	更新公司名称	17.07.10	MM	ANGLES: X° REF±6°	APPROVED: [Signature]	伍文聪	17.07.10		
			MM	0.00±0.15				DWG. NO:	
			MM	X° ±3°				ENDE05	
			MM	0.00±0.08				REV: C1	
			MM	X° X'±2°				SHEET: 1/1	