



12019H00-NPX-HF
① ② ③④ ⑤

- ① Series No.
- ② H90 : Side Contact
H00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)
Blank : Natural type
- ⑤ HF : Halogen Free

Specifications:
 Rated Voltage : 125V AC/DC
 Rated Current : 2A AC,DC
 Withstand Voltage : 500V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 Insulator: Nylon66 UL94V-0 Halogen Free.
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Circuit	Dimensions		
	A	B	C
2P	--	5.10	5.80
3P	4.00	7.10	7.80
4P	6.00	9.10	9.80
5P	8.00	11.10	11.80
6P	10.00	13.10	13.80
7P	12.00	15.10	15.80
8P	14.00	17.10	17.80
9P	16.00	19.10	19.80
10P	18.00	21.10	21.80
11P	20.00	23.10	23.80
12P	22.00	25.10	25.80
13P	24.00	27.10	27.80
14P	26.00	29.10	29.80
15P	26.00	31.10	31.80



Part No.	Material	Color
12019H00-NP-HF	Nylon 66,UL94V-0	Natural
12019H00-NPA-HF	Nylon 66,UL94V-0	Black

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 JCTC [®] TERMINAL&CONNECTORS
AO	Initial Release	2021.7.08	LINEAR	ANGLES	1:1	Nelson	21.07.08	12019H00-NPX-HF	ENDE05	
			0.0±0.25	X° REF±6°	APPROVED					
			0.00±0.15	X° ±3°	DESIGNER	ML	21.07.08	TITLE		
			0.000±0.08	X° X' ±2°	DRAWN	JIA	2021.7.08	2.0mm PITCH HOUSING		
			UNIT: MM							
			SIZE: A4							