



Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Dimensional Ordering Information:		
Part No Circuits	Dimensions	
	A	B
2P	2.50	7.00
3P	5.00	9.50
4P	7.50	12.00
5P	10.00	14.50
6P	12.50	17.00
7P	15.00	19.50
8P	17.50	22.00
9P	20.00	24.50
10P	22.50	27.00
11P	25.00	29.50
12P	27.50	32.00
13P	30.00	34.50
14P	32.50	37.00
15P	35.00	39.50

- 12502H00-NP-HF-NK
 ① ② ③ ④ ⑤
- ① Series No.
 - ② H90 : Side Contact
H00 : Up Contact
 - ③ No. of Circuits
 - ④ HF : Halogen Free
 - ⑤ NK : No mark

Suitable for JCTC 12502 series terminal



Part No.	Material	Color
12502H00-NP	Nylon 66,UL94V-0	Natural(White)
12502H00-NP-HF	Nylon 66,UL94V-0	Natural(White)
12502H00-NPA-HF	Nylon 66,UL94V-0	Black
12502H00-NPC-HF	Nylon 66,UL94V-0	RED
12502H00-NP-HF-NK	Nylon 66,UL94V-0	Natural(White)

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE:	NAME	DATE
C0	换图框发行	10.11.23			LINEAR	ANGLES	1:1	
C1	HN1104190062	11.04.07		0.0±0.25	X° REF±6°	APPROVED		
C2	HN1207050044	12.07.05		0.00±0.15	X° ±3°	DESIGNER		
C3	依HN1801020001新增规格	18.01.02	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	罗春成	18.01.02

JCTC 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司		PART NO: 12502H00-NP-XX-XX	
TITLE: EH 2.50mm PITCH HOUSING		DWG. NO: ENDE05	
REV:	C3	SHEET:	1/1