



12505H00-3P-L-S1-HF
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② H00 : Up Contact
- ③ No. of Circuits
- ④ L: With Lock
- ⑤ S1: Appropriate Customer
- ⑥ HF: Halogen Free

Specifications:
 Voltage Rating : 250V AC/DC
 Current Rating : 6A AC/DC (AWG#16-#18)
 Withstand Voltage : 1000V AC/minute
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements



Suitable for JCTC 12505 and 11501 series terminal

Part No.	Material	Color
12505H00-3P-L-S1-HF	Nylon 66,UL94V-0	白色(白色)
12505H00-3PE-L-S1-HF	Nylon 66,UL94V-0	黄色

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO:
A0	新图面发行	15. 04. 02	SIZE: A4	LINEAR	1:1	APPROVED			
A1	新增黄色规格	15. 11. 18		0.0±0.25		DESIGNER			DWG. NO:
A2	更新公司名称	17. 04. 07		0.00±0.15		DRAWN			ENDE05
A3	HR1911250281	19. 11. 25		0.000±0.08					REV: A3 SHEET: 1/1
									TITLE: 2.50mm Pitch Housing (Special)