



12541H00-NPX-HF

① ② ③④ ⑤

- ① Series No.
- ② H90 : Side Contact
H00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)
Blank : Natural type
- ⑤ HF : Halogen Free

A : Black B : Brown C : Red
D : Orange E : Yellow F : Green
G : Blue H : Purple K : White

Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 Pitch Between Poles : 2.54mm
 The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements

Circuits Part No	Dimensions	
	A	B
01P	---	2.54
02P	---	5.08
03P	5.08	7.62
04P	7.62	10.16
05P	10.16	12.70
06P	12.70	15.24
07P	15.24	17.78
08P	17.78	20.32
09P	20.32	22.86
10P	22.86	25.40
11P	27.94	27.94
12P	30.48	30.48

Suitable for JCTC 12541 series terminal

Part No.	Material	Color	备注
12541H00-NPA-HF	Nylon 66,UL 94V-0	黑色无卤	---
12541H00-NP-HF	Nylon 66,UL 94V-0	本色无卤	---

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART. NO: 12541H00-NPX-HF	DWG. NO: ENDE05	 TERMINAL&CONNECTORS
C0	新图面发行	10. 10. 06		LINEAR	ANGLESp3	APPROVED					
C1	新增黑色规格	13. 10. 16	0. 00±0. 25	X° REF±6°	DESIGNER	TITLE: DB 单排 2.54mm PITCH HOUSING	REV: C2	SHEET: 1/1			
C2	更新图框	20. 03. 06	UNIT: MM	0. 00±0. 15	X° ±3°	DRAWN	伍文聪	20. 03. 06			
			SIZE: A4	0. 000±0. 08	X° X' ±2°						