



PART NO  
12541T2P-XX-61

Finish

CA--Gold-flash	OB--2u"	OC--3u"
OD--4u"	OE--5u"	OF--10u"
OG--15u"	OH--30u"	OI--50u"

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
12541T2P-2E-61	AWG #22~#28	1.60mm(max)	Phosphor Bronze	Tin-plated	10,000 pcs
12541T2P-0X-61	AWG #22~#28	1.60mm(max)	Phosphor Bronze	Gold-plated	10,000 pcs
12541T2P-0A-61-01	AWG #22~#28	1.60mm(max)	Phosphor Bronze	Au:1u"Min	10,000 pcs

The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE:	NAME	DATE	PART. NO:	DWG. NO:	 <b>JCTC</b> ® TERMINAL&CONNECTORS
C2	TN1310090165	13. 10. 10		LINEAR	1:1	APPROVED		12541T2P-XX-61	ENDE05	
C3	整理图面	15. 06. 29		ANGLES		DESIGNER				
C4	变更公司名称	17. 03. 15	UNIT: MM	0.00±0.15	X° REF±6°			TITLE: 杜邦2.54高脚端子		
C5	TN2006130118	17. 03. 15	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	陈佳龙		20. 06. 13	