



Specifications:  
 Rated Voltage : 250V AC/DC  
 Rated Current : 2A AC,DC  
 Withstand Voltage : 800V AC/minute  
 Contact Resistance : 20mΩ(MAX.)  
 Insulation Resistance : 1000MΩ(MIN.)  
 Temperature Range : -25°C~+85°C  
 Pitch Between Poles : 2.00mm  
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

22001H90-NPX-HF-NK  
 ① ② ③④⑤ ⑥

- ① Series No.
- ② H90 : Side Contact  
H00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)  
A : Black type  
E : Yellow type
- ⑤ HF : Halogen Free
- ⑥ NK : No Mark  
Blank : Marnk

Circuits No.	Dimensions	
	A	B
2P	2.00	5.20
3P	4.00	7.20
4P	6.00	9.20
5P	8.00	11.20
6P	10.00	13.20
7P	12.00	15.20
8P	14.00	17.20
9P	16.00	19.20
10P	18.00	21.20
11P	20.00	23.20
12P	22.00	25.20
13P	24.00	27.20
14P	26.00	29.20
15P	28.00	31.20
16P	30.00	33.20
17P	32.00	35.20
18P	34.00	37.20
19P	36.00	39.20
20P	38.00	41.20

Suitable for JCTC 22001 series terminal

Part No.	Material	Color
22001H90-NP	Nylon 66,UL94V-0	本色
22001H90-NP-HF	Nylon 66,UL94V-0	无卤材料
22001H90-NPE-HF	Nylon 66,UL94V-0	黄色无卤
22001H90-NP-NK	Nylon 66,UL94V-0	本色
22001H90-NP-HF-NK	Nylon 66,UL94V-0	无卤材料
22001H90-NPA-HF	Nylon 66,UL94V-0	黑色无卤

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	<b>JCTC</b> ® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO:
C3	HN1207060045	12. 07. 06		LINEAR	ANGLES	APPROVED				22001H90-NPX-XX-XX
C4	HN1309270161	13. 09. 27	0. 00±0. 15	X° REF±6°	DESIGNER	TITLE:	伍文聪	17. 05. 12	SAN 2. 00mm PITCH HOUSING	DWG. NO:
C5	新增黑色规格	16. 12. 12	0. 000±0. 08	X° X'±2°	DRAWN					ENDE05
C6	HR1705020052	17. 05. 12	SIZE: A4							REV: C6 SHEET: 1/1