



Dimensional Ordering Information:							
Circuits No.	Dimensions						
	A	B	C	D	E	F	G
2P	1.25	4.40	2.75	3.35		2.30	1.10
3P	2.50	5.65	4.00	4.60		3.55	1.95
4P	3.75	6.90	5.25	5.85		4.80	3.20
5P	5.00	8.15	6.50	7.10		5.40	3.20
6P	6.25	9.40	7.75	8.35		5.40	3.20
7P	7.50	10.65	9.00	9.60		6.55	3.20
8P	8.75	11.90	10.25	10.85		6.55	3.20
9P	10.00	13.15	11.50	12.10		6.55	3.20
10P	11.25	14.40	12.75	13.35		5.40	3.20
11P	12.50	15.65	14.00	14.60	11.5	7.00	4.50
12P	13.75	16.90	15.25	15.85	11.5	7.00	4.50
13P	15.00	18.15	16.50	17.10	11.5	7.00	4.50
14P	16.25	19.40	17.75	18.35	11.5	7.00	4.50
15P	17.50	20.65	19.00	19.60	11.5	7.00	4.50
20P	23.75	26.90	25.25	25.85	11.5	7.00	4.50
22P	26.25	29.40	27.75	28.35	11.5	7.00	4.50
25P	30.00	33.15	31.50	32.10	11.95	7.90	5.70
30P	36.25	39.40	37.75	38.35	11.95	7.90	5.70

11253H00-NPX-L-HF
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② H90 : Side Contact
- ③ No. of Circuits
- ④ A: Product color (A-Y)
- Blank: Natural type
- ⑤ L : Mount type
- ⑥ HF : Halogen Free



Suitable for JCTC 11256TOP-XX-XX series terminal

Part No.	Material	Color
11253H00-NP-L	Nylon 66,UL94V-0	本色
11253H00-NP-L-HF	Nylon 66,UL94V-0	无卤本色
11253H00-NPA-L-HF	Nylon 66,UL94V-0	无卤黑色

Specifications:
 Rated Voltage : 125V AC/DC
 Rated Current : 1A AC,DC
 Withstand Voltage : 250V AC/minute
 Contact Resistance : 30mΩ(MAX.)
 Insulation Resistance : 100MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 Pitch Between Poles : 1.25mm
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO:
C4	HN1109050128	11.09.05	LINEAR	1:1				11253H00-NPX-L-XX
C5	HN1407020099	14.07.02	ANGLES	APPROVED				
C6	变更公司名称	17.03.14	0.0±0.25 X° REF±6°	DESIGNER				
D0	HN1908060176	19.07.29	0.00±0.15 X° ±3°	DRAWN	张振坤	19.07.29		
			0.000±0.08 X° X'±2°	TITLE: DF14带扣 1.25mm PITCH HOUSING			REV: D0	SHEET: 1/1