



Specifications:
 Rated Voltage : 100V AC/DC
 Rated Current : 2A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Circuits No.	Dimensions		
	A	B	C
2P	2.00	5.70	4.60
3P	4.00	7.70	6.60
4P	6.00	9.70	8.60
5P	8.00	11.70	10.60
6P	10.00	13.70	12.60
7P	12.00	15.70	14.60
8P	14.00	17.70	16.60
9P	16.00	19.70	18.60
10P	18.00	21.70	20.60
11P	20.00	23.70	22.60
12P	22.00	25.70	24.60
13P	24.00	27.70	26.60
14P	26.00	29.70	28.60
15P	28.00	31.70	30.60
16P	30.00	33.70	32.60

- 12001H00-NPX-S1-HF
 ① ② ③④ ⑤ ⑥
- ① Series No.
 - ② H90 : Side Contact
H00 : Up Contact
 - ③ No. of Circuits
 - ④ A : Black
 - ⑤ S1 : S1 Type
 - ⑥ HF : Halogen Free



Suitable for JCTC 12001 series terminal

Part No.	Material	Color
12001H00-NP-S1	Nylon 66,UL94V-0	本色
12001H00-NP-S1-HF	Nylon 66,UL94V-0	本色(无卤)
12001H00-NPA-S1-HF	Nylon 66,UL94V-0	黑色(无卤)

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART. NO: 12001H00-NPX-S1-HF
C3	调整图面“HF”方向	11.05.27	LINEAR	1:1	APPROVED			
C4	C尺寸加大0.05mm	14.03.27	ANGLES	0.0±0.25	DESIGNER			
C5	增加黑色规格	15.07.27	0.00±0.15	X° REF±6°	DRAWN			
C6	更新公司名称	17.12.01	0.000±0.08	X° X'±2°				