



Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

12002H00-NPX-L-HF-NK
 ① ② ③④⑤⑥ ⑦

- ① Series No.
- ② H90 : Side Contact
H00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)
Blank : Natural type
- ⑤ L : Mount type
- ⑥ HF : Halogen Free
- ⑦ NK : No Mark



Circuits No.	Dimensions				
	A	B	C	D	E
2P	--	4.30	6.00	2.00	
3P	4.00	6.30	8.00	3.30	
4P	6.00	8.30	10.00	4.50	
5P	8.00	10.30	12.00	4.50	7.80
6P	10.00	12.30	14.00	4.50	7.80
7P	12.00	14.30	16.00	4.50	7.80
8P	14.00	16.30	18.00	4.50	7.80
9P	16.00	18.30	20.00	4.50	7.80
10P	18.00	20.30	22.00	11.00	14.30
11P	20.00	22.30	24.00	11.00	14.30
12P	22.00	24.30	26.00	11.00	14.30
13P	24.00	26.30	28.00	11.00	14.30
14P	26.00	28.30	30.00	11.00	14.30
15P	28.00	30.30	32.00	11.00	14.30
16P	30.00	32.30	34.00	11.00	14.30

Suitable for JCTC 12002 series terminal

Part No.	Material	Color
12002H00-NP-L-HF	Nylon 66,UL94V-0	Natural(White)
12002H00-NPA-L-HF	Nylon 66,UL94V-0	Black
12002H00-NP-L-HF-NK	Nylon 66,UL94V-0	Natural(White)

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE
C6	HN1105210079	11.05.21	LINEAR 0.0±0.25	1:1	张振坤	20.11.09
D0	新增无Mark规格	12.11.22				
D1	HN1312040212	13.12.05	0.00±0.15	APPROVED	张振坤	20.11.09
D2	换图框发行	20.11.09				

PART NO:	12002H00-NPX-L-HF-XX	DWG NO:	ENDE05
TITLE:	PA 2.0mm PITCH HOUSING 单排带扣		

JCTC[®]
 TERMINAL&CONNECTORS
 REV: D2 SHEET: 1/1