



PART NO.	Dimensions	
	A	B
2x2	--	6.00
2x3	4.00	8.00
2x4	6.00	10.00
2x5	8.00	12.00
2x6	10.00	14.00
2x7	12.00	16.00
2x8	14.00	18.00
2x9	16.00	20.00
2x10	18.00	22.00
2x11	20.00	24.00
2x12	22.00	26.00
2x13	24.00	28.00
2x14	26.00	30.00
2x15	28.00	32.00
2x16	30.00	34.00
2x17	32.00	36.00
2x18	34.00	38.00
2x19	36.00	40.00
2x20	38.00	42.00

Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

- 12002W00-2XNPX-5A-HF
 ① Series No.
 ② W90 : Side Contact
 W00 : Up Contact
 ③ No. of Circuits
 ④ X : Product color(A--Y)
 Blank : Natural type
 ⑤ 5A : Gold-flash
 ⑥ HF : Halogen Free

Part No.	Material	Color	PIN Material
12002W00-2XNP	Nylon 66,UL94V-0	灰色	Brass/Tin-plated
12002W00-2XNP-5A	Nylon 66,UL94V-0	灰色	Brass/Gold-flash
12002W00-2XNPJ	Nylon 66,UL94V-0	灰色	Brass/Tin-plated
12002W00-2XNP-HF	Nylon 66,UL94V-0	本色(白色)	Brass/Tin-plated
12002W00-2XNP-5A-HF	Nylon 66,UL94V-0	本色(白色)	Brass/Gold-flash

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	JCTC ® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART NO:
C1	TN1007150043	10.07.15	LINEAR	1:1				12002W00-2XNPX-XX
C2	新增本色无卤规格	13.02.18	0.0±0.25	APPROVED				DWG NO:
C3	新增2xNPJ规格	16.05.20	X° REF±6°	DESIGNER				ENDE05
C4	依WR1704280044增加镀全金1u~规格	17.04.28	UNIT: MM 0.00±0.15	X° ±3°	17.09.12		REV: C4	
			SIZE: A4 0.000±0.08	X° X'±2°	伍文聪	17.04.28	SHEET: 1/1	