





Specifications:
 Voltage Rating : 500V AC/DC
 Withstand Voltage : 1500V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(Min.)
 Terminal Retention : 3.00Kg/f Min.
 Suitable for 1.07mm PIN



Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
34202TOP-2E-F	AWG #18~#22	2.10mm(max)	Copper alloy	Ni 50u" Min.,Tin plated 80u" Min.电测测点2	4,000 pcs
34202TOP-3E-F	AWG #18~#22	2.10mm(max)	Copper alloy	Ni 50u" Min.,Tin plated 80u" Min.电测测点2	4,000 pcs
34202TOP-0G-F	AWG #18~#22	2.10mm(max)	Copper alloy	Ni 50u" Min.,Gold plated 15u" Min.电测测点2	4,000 pcs
34202TOP-3E-2-F	AWG #18~#22	2.10mm(max)	Copper alloy	Ni 50u" Min.,Tin plated 80u" Min.电测测点1	4,000 pcs
34202TOP-0H-G-F	AWG #18~#22	2.10mm(max)	Copper alloy	Ni 50u" Min.,Gold plated 30u" Min.电测测点1	4,000 pcs

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	PART. NO.:	DWG. NO.:	 TERMINAL&CONNECTORS
C0	新图面发行	13.12.04	LINEAR	1:1			34202TOP-XX-X-X	ENDE05	
C1	修改凸包、倒扣尺寸公差	15.03.26	ANGLES	APPROVED	张振坤	2009.10	TITLE: 4.20mm Pitch Crimp Terminal	REV: C3 SHEET: 1/1	
C2	变更公司名称	17.03.27	0.0±0.25 X° REF±6°	DESIGNER	张振坤	2009.10			
C3	新增规格	20.08.14	0.00±0.15 X° ±3°	DRAWN	张振坤	20.08.14			
			UNIT: MM 0.00±0.08 X° X'±2°						