




RoHS



SECTION: A-A





SEC: A-A
SCALE: 2.5:1



Specifications:
 Rated Voltage : 30V AC/DC
 Rated Current : 0.5A AC,DC
 Withstand Voltage : 200V AC/minute
 Contact Resistance : 30mΩ(MAX.)
 Insulation Resistance : 100MΩ(MIN.)
 Temperature Range : -25°C~+85°C


Dimensional Ordering Information:			
Circuits Part No	Dimensions		
	A	B	C
2P	0.80	3.20	1.78
3P	1.60	4.00	2.58
4P	2.40	4.80	3.38
5P	3.20	5.60	4.18
6P	4.00	6.40	4.98
7P	4.80	7.20	5.78
8P	5.60	8.00	6.58
9P	6.40	8.80	7.38
10P	7.20	9.60	8.18
11P	8.00	10.40	8.98



50801H00-NPX-T5A-XX-34

① ② ③④⑤⑥⑦ ⑧

- ① Series No.
- ② H90 : Side Contact
H00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)
Blank : Natural type
- ⑤ T : Mount type
- ⑥ 5A : Gold-flash
- ⑦ HF : Halogen Free
- ⑧ 34 : AWG #34



Applicable Wire: AWG #34(Insulation O.D.: 0.32mm)

Part No.	Material	Color	Terminal Material	备注
50801H00-NP-T5A-34	Nylon 46,UL94V-0	本色	Phosphor Bronze/Gold-flash	镀全金1u"
50801H00-NP-T5A-HF-34	Nylon 66,UL94V-0	本色无卤	Phosphor Bronze/Gold-flash	镀全金1u"
50801H00-NPA-T5A-HF-34	Nylon 66,UL94V-0	黑色无卤	Phosphor Bronze/Gold-flash	镀全金1u"

REV.	REVISION RECORD	DATE	UNIT: MM	SIZE: A4	GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	TITLE	PART. NO:	DWG. NO:	REV:	SHEET:
C0	换图框发行	10.11.08			LINEAR	1:1			JSTC ® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	50801H00-NPX-T5A-XX-34	ENDE05	C3	1/1
C1	新增无卤规格	10.11.22		0.0±0.25	ANGLES	APPROVED							
C2	新增黑色无卤规格	13.06.13		0.00±0.15	X° REF±6°	DESIGNER	17.03.20						
C3	变更公司名称	17.03.20		0.000±0.08	X° X'±2°	DRAWN	卢小锋						
TITLE: JST0.8 刺破0.80mm PITCH HOUSING													