



技术要求:

1. 塑件表面光洁, 无毛刺, 明显收缩, 缺陷, 裂纹等现象
2. 插针表面电镀光亮, 无斑纹, 划痕
3. 温度范围: -25°C 85°C ;
4. 额定电压: 125V, AC,DC;
5. 额定电流: 1A, AC,DC
6. 接触电阻: $\leq 20\text{m}\Omega$;
7. 绝缘电阻: $\geq 500\text{M}\Omega$;
8. 耐压: 500V, AC/minute

NO. OF Contacts (n)	Dimensions	
	A	B
2	1.0	4.0
3	2.0	5.0
4	3.0	6.0
5	4.0	7.0
6	5.0	8.0
7	6.0	9.0
8	7.0	10.0
9	8.0	11.0
10	9.0	12.0
11	10.0	13.0
12	11.0	14.0
13	12.0	15.0
14	13.0	16.0
15	14.0	17.0
16	15.0	18.0
17	16.0	19.0
18	17.0	20.0
19	18.0	21.0
20	19.0	22.0



11008W90-NP-S-W1

① ② ③ ④ ⑤

- ① Series No.
- ② W90 : Side Contact
W00 : Up Contact
- ③ No. of Circuits
- ④ S : SMT TYPE
- ⑤ W1: W1 TYPE

The product using material and processing must conform to the "W1-PZ-142"HSF technical standard control requirements

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE:	NAME	DATE	Part No.	Insulator	Contact	PART. NO:
C1	新增PIN 位	16.06.08	LINEAR	ANGLES	1:1			11008W90-NP-S-W1	LCP UL94V-0/Natural(Beige)	Phosphor Bronze/Matte-Tin	11008W90-NP-S-W1
C2	WR1905270095	18.11.20	0.0±0.25	X° REF±6°	APPROVED	[Signature]					
			UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	[Signature]				DWG. NO:
			SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	[Signature]				ENDE05
											REV: C2
											SHEET: 1/1

JGTC 胜蓝科技股份有限公司
TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司

TITLE: 11008W90-NP-S-W1 卧贴带扣